

BOSS® 240 Pipe Sealant with PTFE

THE EFFECTIVE & DEPENDABLE SEALANT

BOSS® 240 Pipe Sealant with PTFE merges the high performance of an anaerobic sealant with the lubricity of PTFE to form a dependable, highly chemical resistant, single component sealant. BOSS® 240 is packaged in convenient 50ml and 250ml squeeze tubes with a flip top, ribbon applicator that allows for faster, more uniform application.

SOME OTHER ADVANTAGES ARE:

- Seals all metals including stainless steel and aluminum
- Needs no primer
- Acts as a lubricant for parts during assembly
- Allow 30 minutes for readjustment of parts
- One tube provides up to 400 applications (1/8" pipe)
- Resistant to gasoline, petroleum oil, natural gas, butane and propane
- Outperforms teflon tapes
- Seals to burst rate of pipe



TYPICAL PROPERTIES

Uncured

Color white
 Specific Gravity 1.05 gm/cc
 Particle Size 40 Micron
 Viscosity 450,000 cps
 Flash Point 860°F
 Temperature Range -65°F to +300°F
 Storage Stability +12 months @ <75°F

Cured

Cure Speed 4 hours
 Locking Torque 500 in.-lbs. (1/2" NPT Pipe)
 Instant Sealing >200 psig
 Chemical Resistance Excellent
 Pressure Resistance 10,000 psi

*Information on this data sheet is subject to change without notice and should not be used for writing specifications. For additional information on specific applications, contact Accumetric, LLC

PIPE SEALANT CHART

Fittings per 50ml

Pipe Diameter in inches	Manual Application
1/8" NPT	400
1/4" NPT	200
3/8" NPT	133
1/2" NPT	100
3/4" NPT	67
1" NPT	50

These figures represent typical uses and should only be used as a guideline for your specific application

MADE IN U.S.A.

BOSS® PRODUCTS

Accumetric, LLC
 350 Ring Road Elizabethtown, KY 42701
 800-928-BOSS(2677) 270-769-3385 FAX 270-765-2412
 www.accumetricinc.com

CAUTION: Eye irritant. May irritate sensitive skin. Contains Methacrylic Esters. Avoid contact with eyes and skin. In case of contact, flush eyes immediately with water. Call a physician. Wash skin after contact.